

## Grass Trimmer/Brush Cutter Operator's Manual

MODEL

SRM-211 🖍

Serial Number 06001001 - 06999999

## WARNING \Lambda DANGER

The muffler or catalytic muffler and surrounding cover may become extremely hot. Always keep clear of exhaust and muffler area, otherwise serious personal injury may occur.

## WARNING

The engine exhaust from this product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.



Read rules for safe operation and instructions carefully. ECHO provides an Operator's Manual and a Safety Manual. Both must be read and understood for proper and safe operation.

X7712270401

X771000051 11/02



## INTRODUCTION

Welcome to the ECHO family. This ECHO product was designed and manufactured to provide long life and on-the-job dependability. Read and understand this manual and the SAFETY MANUAL you found in the same package. You will find both easy to use and full of helpful operating tips and SAFETY messages.

## THE OPERATOR'S MANUAL

Read and understand this manual before operation. Keep it in a safe place for future reference. Contains specifications and information for operation, starting, stopping, maintenance, storage and assembly specific to this product.



#### THE SAFETY MANUAL

Read and understand this manual before operation. Keep it in a safe place for future reference. Explains possible hazards involved with the use of Grass Trimmers and Brush Cutters and what measures you should take to make their use safer.

## TABLE OF CONTENTS

Operation ...... 17 - Stopping Engine ..... 19 Maintenance ...... 19 - Maintenance Intervals ...... 20 Spark Plug ...... 22 --Additional or Replacement Manuals ...... 32

Specifications, descriptions and illustrative material in this literature are as accurate as known at the time of publication, but are subject to change without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment.

Copyright© 2002 By Echo, Incorporated All Rights Reserved.


## MANUAL SAFETY SYMBOLS AND IMPORTANT INFORMATION

Throughout this manual and on the product itself, you will find safety alerts and helpful, information messages preceded by symbols or key words. The following is an explanation of those symbols and key words and what they mean to you.



This symbol accompanied by the words **WARNING** and **DANGER** calls attention to an act or condition that can lead to serious personal injury to operator and bystanders.

The circle with the slash symbol means whatever is shown within the circle is prohibited.




**IMPORTANT** The enclosed message provides information necessary for the protection of the unit.

**NOTE** This enclosed message provides tips for use, care and maintenance of the unit.

## SAFETY

## DECALS

Locate these safety decals on your unit. The complete unit illustration, found in the "DESCRIPTION" section, will help you locate them. Make sure the decals are legible and that you understand and follow the instructions on them. If a decal cannot be read, a new one can be ordered from your ECHO dealer. See PARTS ORDERING instructions for specific information.



#### Shaft Decal <u>Spanish Decal</u>

**ADVERTENCIA PELIGRO** Esta unidad puede ser peligrosa y producir lesiones personales graves si no se usa en forma adecuada. Para reducir el riesgo de lesionarse, los operadores, los ayudantes y los espectadores deben leer y comprender el Manual Del Operador y los Manuales De Seguridad que se entregan escritos en español.

## 

DANGER

This unit can be dangerous and cause serious injury if improperly used. to reduce injury risk to operator, helpers and bystanders, read and understand the Operator's and Safety Manuals, which are provided in Spanish.




#### Shaft Decal



- This unit can be dangerous and cause serious injury if improperly used. To reduce injury risk to operator, helpers and bystanders, read and understand the Operator's and Safety manuals.
- Blindness can occur from objects that are thrown or ricocheted even with shield in place. Operators, helpers and bystanders must wear ANSI Z87.1 approved eye protection.
- Always wear hearing protection when operating unit.
- Prevent accidental contact with unit and any cutting attachment. Maintain a 50 ft. (15M) radius, DANGER ZONE surrounding the operator. **ONLY** the operator, dressed in proper protective clothing should be in the DANGER ZONE.
- Beware of KICKOUT (blade thrust) when using blades. Special precautions are necessary for blade operation, see your Operator's and Safety Manuals. ONLY install ECHO approved blades on Brush Cutters (SRM) models equipped with proper blade shield, U-handles, harness, blade collar, nut and cotter pin.
- · Blade/Cutting attachment does not stop immediately after releasing throttle. Keep hands and feet clear of blade/cutting attachment unless engine is shut off and cutting attachment is not moving.
- INSPECT BLADES BEFORE USE.
- DONOTUSE DAMAGED, CRACKED, BENT, DULLOR IMPROPERLY SHARPENED BLADES.
- Do not remove shields, modify the unit or install attachments or parts not approved by ECHO. Approved attachment information and replacement Operator's and Safety Manuals are available from your ECHO dealer or by writing: ECHO, INCORPORATED, 400 OAKWOOD RD., LAKE ZURICH, IL 60047.

## INTERNATIONAL SYMBOLS



#### Symbol description/application Symbo Symbol form/shape Symbol form/shape Fuel and oil mixtu Emergency stop STOP + Carburetor adjustment Primer Bulb ΗП ▶€∰ High speed mixture Ignition Carburetor adjust - Idle speed Ignition ON/OFF ON OFF Ο Choke Control Carburetor adjustmen 'Cold Start" - Low speed mixture Position (Choke Closed) Choke Control "Run" Position (Choke Open)

P/N 89016054130













## **S**AFETY **I**NSTRUCTIONS PERSONAL CONDITION AND SAFETY EQUIPMENT



Trimmer/Brush Cutter users risk injury to themselves and others if the trimmer/brush cutter is used improperly or safety precautions are not followed. Proper clothing and safety gear must be worn when operating a trimmer/brush cutter.

#### Physical Condition

Your judgment and physical dexterity may not be good:

- if you are tired or sick,
- if you are taking medication,
- if you have taken alcohol or drugs.

Operate unit only if you are physically and mentally well.

#### Eye Protection

Wear eye protection that meets ANSI Z87.1 or CE requirements whenever you operate the trimmer.

#### Hand Protection

Wear no-slip, heavy duty work gloves to improve your grip on the Trimmer/Brush Cutter handles. Gloves also reduce the transmission of machine vibration to your hands.

#### **Hearing Protection**

ECHO recommends wearing hearing protection whenever unit is used.

#### **Proper Clothing**

Wear snug fitting, durable clothing;

- Pants should have long legs, shirts with long sleeves.
- DONOT WEAR SHORTS,
- DONOT WEAR TIES, SCARVES, JEWELRY.

Wear sturdy work shoes with non-skid soles;

- DONOT WEAR OPEN TOED SHOES,
- DONOT OPERATE UNIT BAREFOOTED.

### **EXTENDED OPERATION/EXTREME CONDITIONS**

#### Vibration and Cold

It is believed that a condition called Raynaud's Phenomenon, which affects the fingers of certain individuals, may be brought about by exposure to vibration and cold. Exposure to vibration and cold may cause tingling and burning sensations, followed by loss of color and numbness in the fingers. The following precautions are strongly recommended, because the minimum exposure which might trigger the ailment is unknown.

- Keep your body warm, especially the head, neck, feet, ankles, hands, and wrists.
- Maintain good blood circulation by performing vigorous arm exercises during frequent work breaks, and also by not smoking.
- Limit the hours of operation. Try to fill each day with jobs where operating the trimmer or other hand-held power equipment is not required.
- If you experience discomfort, redness and swelling of the fingers followed by whitening and loss of feeling, consult your physician before further exposing yourself to cold and vibration.




# 6 **[[[EEHD**<sub>®</sub>

#### **Repetitive Stress Injuries**

It is believed that overusing the muscles and tendons of the fingers, hands, arms and shoulders may cause soreness, swelling, numbness, weakness, and extreme pain in those areas. Certain repetitive hand activities may put you at a high risk for developing a Repetitive Stress Injury (RSI). An extreme RSI condition is Carpal Tunnel Syndrome (CTS), which could occur when your wrist swells and squeezes a vital nerve that runs through the area. Some believe that prolonged exposure to vibration may contribute to CTS. CTS can cause severe pain for months or even years.

To reduce the risk of RSI/CTS, do the following:

- Avoid using your wrist in a bent, extended, or twisted position. Instead, try to maintain a straight wrist position. Also, when grasping, use your whole hand, not just the thumb and index finger.
- Take periodic breaks to minimize repetition and rest your hands.
- Reduce the speed and force with which you do the repetitive movement.
- Do exercises to strengthen the hand and arm muscles.
- Immediately stop using all power equipment and consult a doctor if you feel tingling, numbness, or pain in the fingers, hands, wrists, or arms. The sooner RSI/CTS is diagnosed, the more likely permanent nerve and muscle damage can be prevented.




#### EQUIPMENT



Use only ECHO approved attachments. Serious injury may result from the use of a non-approved attachment combination. ECHO, INC. will not be responsible for the failure of cutting devices, attachments or accessories which have not been tested and approved by ECHO. Read and comply with all safety instructions listed in this manual and safety manual.

- Check unit for loose/missing nuts, bolts, and screws. Tighten and/or replace as needed.
- Inspect fuel lines, tank, and area around carburetor for fuel leaks. DO NOT operate unit if leaks are found.
- Inspect shield for damage and ensure that the cut-off knife is securely in place. Replace if either is damaged or missing.
- Check that the cutting attachment is firmly attached and in safe operating condition.
- Check that front loop handle and shoulder strap/ or shoulder/ waist harness are adjusted for safe, comfortable operation. See Assembly Section for proper adjustment.
- Keep exhaust area clear of flammable debris. Avoid contact during and immediately after operation.



#### **SAFE OPERATION**



Do not operate this product indoors or in inadequately ventilated areas. Engine exhaust contains poisonous emissions and can cause serious injury or death.

Provide all operators of this equipment with the Operator's Manual and instructions for safe operation.

#### Keep A Firm Grip

• Hold the front and rear handles with both hands with thumbs and fingers encircling the handles

#### Keep A Solid Stance

• Maintain footing and balance at all times. Do not stand on slippery, uneven or unstable surfaces. Do not work in odd positions or on ladders. Do not over reach.



## **EMISSION CONTROL**

#### California Tier 2

The emission control system for these engines are EM/TWC (Engine Modification and Catalyst).

IMPORTANT ENGINE INFORMATION ENGINE FAMILY: 2EHXS.0214KA DISPLACEMENT: 21.2 cc EMISSION COMPLIANCE PERIOD : 300 HRS. THIS ENGINE MEETS U.S. EPA PH 2 AND 2000 AND LATER CALIFORNIA EMISSION REGULATIONS FOR S.O.R.E. REFER TO OWNER'S MANUAL FOR MAINTENANCE SPECIFICATIONS AND ADJUSTMENTS.



<u>An Emission Control Label</u> is located on the engine. (This is an EXAMPLE ONLY, information on label varies by engine FAMILY).

#### PRODUCT EMISSION DURABILITY

The 300 hour emission durability compliance period is the time span selected by the manufacturer certifying the engine emissions output meets applicable emissions regulations, provided that approved maintenance procedures are followed as listed in the Maintenance Section of this manual.



## DESCRIPTION

The ECHO product you purchased has been partially assembled for your convenience. Due to packaging restrictions, installation of the plastic debris shield, nylon line head, and positioning of the front handle are necessary.

After opening the carton, check for damage. Immediately notify your retailer or ECHO Dealer of damaged or missing parts. Use the contents list to check for missing parts.

\* Some units may be factory pre-assembled. No assembly tools are needed and the nylon line head, plastic debris shield, and mounting hardware, shown in the contents list, are pre-assembled to the unit. Only the front handle may need to be re-positioned for comfortable operation.

#### CONTENTS


- \_\_\_\_\_1 Power Head / Drive Shaft Assembly
  - \_\_\_\_1 Plastic Bag (co-pack)
- \_\_\_\_\_ 1, Operator's Manual
- \_\_\_\_\_ 1, Safety Manual
- \_\_\_\_\_ 1, Warranty Registration Card
- \_\_\_\_\_ 1, Limited Warranty Statement
- \_\_\_\_\_ 1, Safety Glasses
- \_\_\_\_\_ 1,2-StrokeOilSample
- \* \_\_\_\_\_ 1, Nylon Trimmer Head
- \* \_\_\_\_\_ 1, wrench 17x14.5, P/N X602000030
- \* \_\_\_\_\_ 2, locking tool, P/N 89751801131
- \_\_\_\_ --1, Plastic shield
- \_\_\_\_\_ --1, shield plate
  - \_ --3, 5mm x 16mm screws (shield mtg.)
- \_\_\_\_\_ 1, Large Washer
- \_\_\_\_\_ 1, Split Pin
  - 1, Nut, L.H. M10 x 1.25
    - 12,8 in.x.095 Pre-Cut Nylon Line











# 10 ////EEHD.

- 1. POWER HEAD Includes the Engine, Clutch, Fuel System, Ignition System and Recoil Starter.
- 2. **GRIP** Rear (right hand) handle.
- 3. **THROTTLE TRIGGER LOCKOUT** This lever must be held during starting. Operation of the throttle trigger is prevented unless throttle trigger lockout lever is engaged.
- 4. **STOP SWITCH** "SLIDE SWITCH" mounted on top of the Throttle Trigger Housing. Move switch FORWARD to RUN, BACK to STOP.
- 5. **FRONT HANDLE** The Front (loop) handle is loosely assembled to the Drive Shaft assembly and must be positioned for proper cutting attitude and operator comfort.
- 6. **DRIVE SHAFT ASSEMBLY** Includes the Gear Housing assembly, flex drive cable and Safety Decal.
- 7. NYLON CUTTER HEAD Contains replaceable nylon trimming lines.
- 8. **CUT-OFF KNIFE** Trims line to the correct length (5 in.). If trimmer is operated without a cut-off knife the line may be too long more than (5 in.) the operating speed will slow, the engine overheat and performance will suffer.
- 9. **PLASTIC DEBRIS SHIELD ASSEMBLY** Included in plastic bag (co-pack). **MUST** be installed on unit before use, see Assembly Instructions. Shield assembly includes the Cut-Off Knife. Mounts on the Gear Housing Assembly just above the cutting attachment. Helps protect the operator by deflecting debris produced during the trimming operation. This shield must be replaced with the steel shield for blade use.
- 10. **THROTTLE TRIGGER** Spring loaded to return to idle when released. During acceleration, press trigger gradually for best operating technique.
- 11. SPARK PLUG Provides spark to ignite fuel mixture.
- 12. TOP GUARD Protects arm from the hot engine.
- 13. SPARK ARRESTOR CATALYTIC MUFFLER/MUFFLER The muffler or catalytic muffler controls exhaust noise and emission. The spark arrestor screen prevents hot, glowing particles of carbon from leaving the muffler. Keep exhaust area clear of flammable debris.
- 14. FUEL TANK Contains fuel and fuel filter.
- 15. **RECOIL STARTER HANDLE/ROPE** Pull recoil starter handle/rope using light pulling force, approximately 2/3 (2 ft.) of rope length. Two (2) to Six (6) pulls are required to properly tension starter spring prior to automatic engine engagement. DO NOT let handle snap back or damage to unit will occur.
- 16. FUEL TANK CAP Covers and seals fuel tank opening.
- 17. **PRIMER BULB** Pumping primer bulb before starting engine draws fresh fuel from the fuel tank priming the carburetor for starting. Pump primer bulb until fuel is visible and flows freely in the clear fuel tank return line. Pump bulb an additional 4 or 5 times.
- 18. AIR CLEANER Contains replaceable filter element.
- 19. **CHOKE** The choke control is located on the top of the air filter case. Move choke lever to "Cold Start" to close choke for cold start. Move choke lever to "Run" position to open choke.
- 20. **SAFETY VIDEO** (Not included with unit) P/N 99922202540 English version and P/N 99922203508 Spanish version are available at a cost of \$5.00 from ECHO, INC. or any authorized ECHO dealer. The video overviews safety precautions and proper operating techniques and is supplemental to the Safety Manual. Read and understand the Safety Manual for complete information on safe operation.

## **S**PECIFICATIONS

MODEL	SRM-211 🗾
Length	1778 mm(70.0 in.)
Width	250 mm (9.84 in.)
Height	325 mm(12.8in.)
Weight (dry) w/cutter head	5.4kg(11.9lb.)
Engine Type	Air cooled, two-stroke, single cylinder gasoline engine
Bore	32.2 mm(1.27 in.)
Stroke	26.0 mm(1.02 in.)
Displacement	21.2 cc (1.29 cu. in.)
Exhaust	Spark Arrestor Muffler w/catalyst
Carburetor	Zama model RB w/purge pump
Ignition System	Flywheel magneto, capacitor discharge ignition type
Spark Plug	NGK BPM-8Y Gap 0.65 mm (0.026 in.)
Fuel	Mixed (Gasoline and Two-stroke Oil)
Fuel/Oil Ratio	50:1 ECHO High Performance, two-stroke air cooled engine oil
Gasoline	89 Octane unleaded. DO NOT use fuel containing methyl alcohol,
	more than 10% ethyl alcohol or 15% MTBE.
Oil	50:1 ECHO High Performance, two-stroke air cooled engine oil
Fuel Tank Capacity	0.45 lit. (15.2 US fl. oz.)
Recoil Starter System	Automatic Recoil Starter
Clutch	Centrifugal Type
Drive Shaft	1/4 in. Flex Shaft
Rotating Direction	Counter-Clockwise viewed from top
Cutter Head	Nylon line head (2-line) with .095 line capacity 203mm (8 in.)
Handle*	Front - Loop and Right Rear Handle w/rubber grips
Shoulder Harness	Optional
Idle Speed RPM	2,400-3,200
Wide Open Throttle Speed (W.O.T.) RPM	8,000 - 10,000

\* Install and use U-Handle when operating any model with blade.



## ASSEMBLY

Use only ECHO approved attachments for these models. Serious injury may result from the use of non-approved attachment combinations. Read and comply with all safety instructions listed in this manual and attachment manual.

ECHO, INC. will not be responsible for the failure of cutting devices, attachments or accessories which have not been tested and approved by ECHO for use with these units.

#### PLASTIC SHIELD INSTALLATION

(for Nylon Line Operation)

Tools Required: Screwdriver.

*Parts Required:* Plastic Shield, Shield Plate, three (3) 5mm x 16mm screws.

#### NOTE

The plastic shield is for use with the Nylon Line Head only. Install Metal Shield when using plastic or metal blades.


- 1. Remove plastic sleeve and upper plate (A) from PTO shaft.
- 2. Install the shield on the bottom of the bearing housing flange.
- 3. Place shield plate (B) on shield, align holes and install three (3) 5 x 16 mm screws.
- 4. Install upper plate (A).



Tools Required: Head Locking Tool, 17x19mm Scrench

Parts Required: Nylon Line Head.

- 1. Align hole in upper plate with notch in edge of gear housing and insert head locking tool (C). Remove plastic sleeve from PTO shaft.
- 2. Be sure upper plate (A) remains on PTO shaft.
- 3. Place line head onto PTO shaft. Followed by large metal washer.
- 4. Thread L.H. nut on PTO shaft. Tighten securely.
- 5. Install new split pin.
- 6. Remove locking tool (C).



B

## NYLON LINE INSTALLATION


Tools Required: None

Parts Required: Two (2) Pre-cut Nylon Line 8 in. X .095 in.

- 1. Shut engine off. Lay unit on the ground with head assembly up.
- 2. Remove old nylon line through center recess of head.
- 3. Thread new lines through outside holes (A) in housing until ends meet in center of recess.

NOTE

Insert cutting line ends to center of head recess to insure easy removal of used lines.






### FRONT HANDLE INSTALLATION

Tools Required: Screwdriver.

1. Position front handle for comfortable operation and secure screws.





## **PRE - OPERATION**

## **OPERATION WITH BLADES**

Preparing the Trimmer/Brush Cutter for Blade Use



Blade use **DEMANDS** specific Brush Cutter configuration. Operation without specified shield, harness, and handle can result in serious personal injury.

## Light-Duty Use - Plastic, Nylon, or Metal Blades:


Install Blade Conversion Kit, P/N 99944200415-Includes metal shield (A), barrier bar (B), and shoulder harness (C).


#### NOTE

The Barrier Bar is <u>NOT A HANDLE</u> and should not be gripped when using or carrying the unit.

## *Heavy-Duty Use - Plastic, Nylon, or Metal Blades:*

Install U-Handle / Blade Conversion Kit, P/N 99944200561 - Includes metal shield (A), shoulder harness with hip pad (B), and U-Handles (C).





#### NOTE

The Barrier Bar is used to restrict rearward movement of the unit. For heavy-duty or extended use, U-handles should be used. See your Echo dealer or Trimmer/Brush Cutter Safety Manual for details regarding U-Handles. If you have additional questions, contact your Echo Service Dealer, or call Echo directly at 1-800-673-1558.

#### **Choosing the Correct Blade**



The type of Blade used **MUST** be matched to the type and size of material cut. An improper or dull blade can cause serious personal injury. Blades **MUST** be sharp. Dull blades increase the chance of kick out and injury to yourself and bystanders.

**Plastic/Nylon Blades** may be used where ever the nylon line head is used. DO NOT use this blade for heavy weeds or brush!

**8 Tooth Weed/Grass Blade P/N 69600120331** is designed for grass, garden debris and thick weeds. DO NOT use this blade for brush or heavy woody growth, 19 mm (3/4 in.) diameter or larger.


**Brush/Clearing Blade P/N 69500120331** is designed for cutting brush and woody growth up to 76 mm (3 in.) diameter.

**Use Shoulder/Waist Harness P/N 99944200200** Use of the Shoulder/ Waist Harness is recommended for **ALL** Trimmer/Brush Cutter use, not just Blade operation. The Shoulder/Waist Harness when used in a trimming operation with nylon line head suspends the trimmer from the operator's shoulder and reduces operator fatigue.

During blade operation, the same fatigue reduction is achieved. Safety to the operator is also enhanced by preventing blade contact with the operator's hands and feet by restricting trimmer movement.

#### NOTE

In case of Emergency, pull up on the Quick Release Collar to disconnect the trimmer from the harness.





## FUEL

#### Fuel Requirements

**Gasoline -** Use 89 Octane [R+M/2] (mid grade or higher) gasoline or gasohol known to be good quality. Gasohol may contain up to 10% Ethyl (grain) alcohol or 15% MTBE (methyl tertiary-butyl ether). Gasohol containing methyl (wood) alcohol is **NOT** approved.

**Two Stroke Oil -** A two-stroke engine oil meeting ISO-L-EGD (ISO/CD 13738) and J.A.S.O. <u>FC</u> Standards, must be used. Echo brand Premium 50:1 oil meets these standards. Engine problems due to inadequate lubrication caused by failure to use an ISO-L-EGD and J.A.S.O. <u>FC</u> certified oil, such as Echo Premium 50:1 Two-stroke Oil, will void the two-stroke engine warranty. (Emission related parts <u>only</u> are covered for two years, regardless of two-stroke oil used, per the statement listed in the Emission Defect Warranty Explanation.)

#### IMPORTANT

Echo Premium 2-Stroke Oil may be mixed at 50:1 ratio for application in all Echo engines sold in the past regardless of ratio specified in those manuals.

#### Mixing Instructions

- 1. Fill an approved fuel container with half of the required amount of gasoline.
- 2. Add the proper amount of 2-stroke oil to gasoline.
- 3. Close container and shake to mix oil with gasoline.
- 4. Add remaining gasoline and remix.
- 5. Install fuel container cap and wipe any spilled fuel from container and surrounding area.

#### Handling Fuel

## 

Fuel is **VERY** flammable. Use extreme care when mixing, storing or handling, or serious personal injury may result.

- Use an approved fuel container.
- DO NOT smoke near fuel.
- DO NOT allow flames or sparks near fuel.
- Fuel tanks/cans may be under pressure. Always loosen fuel caps slowly allowing pressure to equalize.
- NEVER refuel a unit when the engine is HOT!
- NEVER refuel a unit with the engine running.
- DO NOT fill fuel tanks indoors. ALWAYS fill fuel tanks outdoors over bare ground.
- Securely tighten fuel cap after refueling.
- Inspect for fuel leakage. If fuel leakage is found, do not start or operate unit until leakage is repaired.

#### IMPORTANT

Spilled fuel is a leading cause of hydrocarbon emissions. Some states may require the use of automatic fuel shut-off containers to reduce fuel spillage. Contact your ECHO dealer for ordering information.

#### After refueling

- Wipe any spilled fuel from the unit.
- Move at least 3 m (10 ft.) from refueling location before starting the engine.

#### After use

• DO NOT store a unit with fuel in its tank. Leaks can occur. Return unused fuel to an approved fuel storage container.

#### Storage

Fuel storage laws vary by locality. Contact your local government for the laws affecting your area. As a precaution, store fuel in an approved, air tight container. Store in a well ventilated, unoccupied building, away from sparks and flames. Do not store fuel longer than 30 days.

#### IMPORTANT

Stored fuel ages. Do not mix more fuel than you expect to use in thirty (30) days, ninety (90) days when a fuel stabilizer is added.

#### IMPORTANT

Stored two-stroke fuel may separate. ALWAYS shake fuel container thoroughly before each use.

## **O**PERATION

## STARTING COLD ENGINE



Cutting attachment will move at high speed when engine is started. Inspect starting area for hazards such as rocks, glass, debris etc. which could be contacted by the cutting attachment when starting. Keep helpers and bystanders at least 15 m (50 ft.) from starting area, otherwise serious personal injury may result.

#### NOTE

Refer to Grass Trimmer/Brush Cutter Safety Manual for proper and safe trimming techniques.

#### 1. Stop Switch

Move stop switch button (A) forward away from the STOP position.

2. Choke

Move choke lever (B) to Cold Start Position (

#### 3. Primer

Pump primer bulb (C) until fuel is visible and flows freely in the clear fuel tank return line. Pump bulb an additional 4 or 5 times.

#### NOTE

Energy is stored in the starter spring each time the handle/rope is pulled. Generally two to six pulls, using light pulling forces, will store enough energy to engage the starter and spin the engine. Do not pull the rope out to end stop.

4. Recoil Starter

Lay the unit on a flat, clear area. Firmly grasp right hand grip and throttle trigger lockout with left hand, and fully depress throttle trigger to wide open position. Gently pull starter handle/rope (D) until engine fires or 2 to 3 engine engagements.

#### 5. Choke


After engine fires or 2 to 3 engine engagements, move choke lever


(B) to Run position ( $\| \buildrel \|$ ). Hold throttle trigger and throttle trigger lockout fully depressed, and pull starter handle/rope until engine starts and runs. Release throttle trigger and allow unit to warm up at idle for several minutes.


#### NOTE

If engine does not start with choke in "Run" position after 5 engine engagements, repeat instructions.

6. After engine warm up, gradually depress throttle trigger to increase engine RPM to operating speed.











#### STARTING WARM ENGINE


The starting procedure is the same as Cold Start except DO NOT close the choke, and do not depress throttle trigger to wide open position.





#### 2. Primer





## **STOPPING ENGINE**

1. Throttle


Release throttle and allow engine to return to idle before shutting off engine.

2. Stop Switch

Move stop switch button (A) backward to STOP position.



position, close choke - COLD START position - to stall engine. Have your ECHO dealer repair stop switch before using trimmer again.



## MAINTENANCE

Your ECHO trimmer is designed to provide many hours of trouble free service. Regular scheduled maintenance will help your trimmer achieve that goal. If you are unsure or are not equipped with the necessary tools, you may want to take your unit to an ECHO Service Dealer for maintenance. To help you decide whether you want to DO-IT-YOURSELF or have the ECHO Dealer do it, each maintenance task has been graded. If the task is not listed, see you Echo Dealer for repairs.

## SKILL LEVELS

- **Level 1** = Easy to do. Most required tools come with unit.
- Level 2 = Moderate difficulty. Some specialized tools may be required.
- **Level 3** = Experience required. Specialized tools are required. ECHO recommends that the unit be returned to your ECHO dealer for servicing.

ECHO offers **REPOWER**<sup>TM</sup> Maintenance Kits and Parts to make your maintenance job easier. Below each task heading are listed the various part numbers required for that task. See your ECHO dealer for these parts.



#### **MAINTENANCE INTERVALS**

COMPONENT/ SYSTEM	MAINTENANCE PROCEDURE	REQ'D SKILL LEVEL	DAILY OR BEFORE USE	EVERY REFUEL	3 MONTHS OR 90 HOURS	6 MONTHS OR 270 HOURS	YEARLY 600 HOURS
	Recommended Ech	o Dealer	Maintenanc	e Procedur	es		
Cylinder Exhaust Port	Inspect/Clean/Decarbon	3			I/C		
	Do-lt-Yourse	If Mainter	nance Proce	dures	1	I	1
Air Filter	Inspect/Clean/Replace	1	I/C		R*		
Choke	Inspect/Clean	2	I/C				
Fuel Filter	Inspect/Replace	1			I		I / R *
Fuel System, leaks	Inspect/Replace	1	I *	Ι	I		
Cooling System	Inspect/Clean	2	I/C				
Muffler Spark Arrestor	Inspect/Replace	2			I / R *		
Drive Shaft (Flex Cable Models)	Grease	2			I (1)		
Gear Housing	Grease	2			I (2)		
Recoil Starter Rope	Inspect/Clean	1	I / C *				
Spark Plug	Inspect/Clean	2			I/C	R *	
Screws/Nuts/Bolts	Inspect/Tighten/Replace	1	I / R *				

MAINTENANCE PROCEDURE LETTER CODES: I = INSPECT, R = REPLACE, C = CLEAN

IMPORTANT NOTE - Time intervals shown are maximum. Actual use and your experience will determine the frequency of required maintenance.

MAINTENANCE PROCEDURE NOTES:

(1) Apply ECHO<sub>®</sub> LUBE™ every 25 hours of use.
(2) Apply ECHO<sub>®</sub> LUBE™ every 50 hours of use.
\* All recommendations to replace are based on the finding of damage or wear during inspection..

## **AIR FILTER**

#### Level 1.

Tools required: 25-50 mm (1-2 in.) Cleaning Brush

*Parts required:* 90008 REPOWER<sup>™</sup> AIR & FUEL FILTER KIT.

- 1. Close choke (Cold Start Position). This prevents dirt from entering the carburetor throat when the air filter is removed. Brush accumulated dirt from the air cleaner area.
- 2. Remove the air cleaner cover. Clean and inspect the element for damage. If element is fuel soaked and very dirty, replace.
- 3. If element can be cleaned and reused, be certain it: •still fits the cavity in the air cleaner cover. •is installed with the original side out.

#### NOTE

Carburetor adjustment may be needed after air filter cleaning/ replacement.

## FUEL FILTER

#### Level 1.


Tools required: 200 - 250 mm (8 - 10 in.) length of wire with one end bent into a hook, Clean rag, funnel, and an approved fuel container

*Parts required:* 90008 REPOWER<sup>™</sup> AIR & FUEL FILTER KIT.




Fuel is **VERY** flammable. Use extreme care when mixing, storing or handling, or serious personal injury may result.

- 1. Use a clean rag to remove loose dirt from around fuel cap and empty fuel tank.
- 2. Use the "fuel line hook" to pull the fuel line and filter from the tank.
- 3. Remove the filter from the line and install the new filter.












### SPARK PLUG


#### Level 2.

*Tools required:* T-Wrench, Feeler gauge (preferably a wire gauge), Soft metal brush

Parts Required: Spark Plug, NGK BPM-8Y P/N 15901019830

- 1. Remove spark plug and check for fouling, worn and rounded center electrode.
- 2. Clean the plug or replace with a new one. DO NOT sand blast to clean. Remaining sand will damage engine.
- 3. Adjust spark plug gap by bending outer electrode.
- 4. Tighten spark plug to 145 155 kg/cm (125 135 in. lb.).





#### **COOLING SYSTEMS CLEANING**

#### Level 2.

*Tools required:* Cross-head screwdriver, 3 mm hex wrench, pointed wood stick, 25 - 50mm (1 - 2 in.) medium bristle paint brush.

Parts Required: None if you are careful.


#### IMPORTANT


To maintain proper engine operating temperatures, cooling air must pass freely through the cylinder fin area. This flow of air carries combustion heat away from the engine.

Overheating and engine seizure can occur when:

- Air intakes are blocked, preventing cooling air from reaching the cylinder.
- Dust and grass build up on the outside of the cylinder. This build up insulates the engine and prevents the heat from leaving.

Removal of cooling passage blockages or cleaning of cooling fins is considered "Normal Maintenance". Any failure attributed to lack of maintenance is not warranted.






- 1. Disconnect spark plug lead from spark plug.
- 2. Release stored energy in power spring by removing spark plug.
- 3. Remove three (3) screws (A) from starter assembly and remove starter.


#### NOTE

DO NOT disassemble the starter assembly.

4. Remove the four screws that retain the engine cover. Two at the inside top of the mounting plate (B), one on the top guard (C), and one at the muffler cover (D).

- 5. Disengage the heat deflector tabs (E) under the muffler from the slots in the engine/muffler cover.
- 6. Lift the cover from the engine.






7. Reinstall spark plug and starter assembly to prevent dirt and debris from entering engine and starter.

#### NOTE

When installing starter housing to mounting body, be sure that drive starter cam engages the starter pawls correctly.







8. Use a brush to remove dirt from the cylinder fins.

#### IMPORTANT


DO NOT use a metal scraper to remove dirt from the cylinder fins.

- 9. Remove grass and leaves from the grid between the starter and fuel tank.
- 10. Reassemble parts in reverse order of removal. When installing the cover, be certain:
  - the tabs of the deflector shield (E) are in the slots of the cover





- the fuel check valve (F) is positioned in the cover
- the spark plug is tightened securely
- the ignition wire (G) is not pinched



## **EXHAUST SYSTEM**

#### Spark Arrestor Screen

#### Level 2.

Tools required: Cross-head screwdriver, soft metal brush.

Parts Required: Screen P/N 14586240630, Gasket P/N V104000360

- 1. Remove engine cover. See "Cleaning Cooling System" pages 22 & 24 for step by step instructions.
- 2. Remove spark arrestor screen cover (A), gasket (B), and screen (C) from muffler body.
- 3. Clean carbon deposits from muffler components.

#### NOTE

When cleaning carbon deposit, be careful not to damage the catalylic body.

- 4. Replace screen if it is cracked, plugged or has holes burned through.
- 5. Assemble components in reverse order.

#### NOTE


When installing the engine cover, be certain the tab of the metal deflector shield is in the slot of the engine cover.


#### Cylinder Exhaust Port


Level 3

#### IMPORTANT

The cylinder exhaust port must be inspected and cleaned of excess carbon every 3 months or 90 hours of operation in order to maintain this engine within the emissions durability period. ECHO strongly recommends that you return your unit to your ECHO dealer for this important maintenance service.









## CARBURETOR ADJUSTMENT

#### Engine Break-In

New engines must be operated for a minimum of two tanks of fuel before carburetor adjustments can be made. During the break-in period, your engine performance will increase and exhaust emissions will stabilize. Idle speed can be adjusted as required.

#### High Altitude Adjustment

High altitude adjustment is not required for proper operation of this engine.

#### Idle Speed Adjustment


Idle speed adjustment may be required periodically to comply with specifications for this unit. See page 11, "Specifications," for correct idle speed.

#### Level 2.

Tools required: Screwdriver, Tachometer (ECHOP/N99051130017).

#### NOTE


Every unit is run at the factory and the carburetor is set in compliance with emission regulations. This carburetor does not have acceleration and high speed adjustment needles.





The cutting attachment should not move at idle. If attachment moves, readjust carburetor according to "Carburetor Adjustment" instructions in this manual or see your ECHO Dealer, otherwise serious personal injury may result.

1. Check idle speed using a tachometer, and reset if necessary. Turn idle screw (A) clockwise to increase idle speed; counter clockwise to decrease idle speed.




#### LUBRICATION

#### Level 1.


*Tools required:* 8 mm Open End Wrench, Cross Head Screwdriver, Clean rag

Parts Required:  $ECHO_{\odot}LUBE^{TM} 8 \text{ oz.} (P/N 91014) \text{ or Lithium Base}$ Grease.



#### Gear Housing

- 1. Clean all loose debris from gear box.
- 2. Remove plug (A) and check level of grease.
- 3. Add grease if necessary, DO NOT over fill.



#### Drive Shaft

- 1. Loosen two (2) screws (B) and remove center locating screw (C). Pull gear box and shield from drive shaft housing.
- 2. Pull flexible cable from the drive shaft housing, wipe clean and recoat with a thin coating [15 ml (1/2 oz.)] of grease.
- 3. Slide the flexible cable back in the drive housing. DO NOT get dirt on the flex cable.
- 4. Install the gear housing and shield assembly.



## SHARPENING METAL BLADES

Three styles of metal blades are approved for use on the ECHO Brush Cutter. The 8-tooth blade can be sharpened during normal maintenance. The clearing blade and 80 tooth blade require professional service.

Before sharpening, CLOSELY inspect blade for cracks (look at the bottom of each tooth and the center mounting hole closely), missing teeth and bending. If ANY of these problems are discovered, replace the blade.

When sharpening a blade, always remove the same amount of materials from each tooth to maintain balance. A blade that is not balanced will cause unsafe handling due to vibration and can result in blade failure.


*Tool required:* Flat file (preferred). Electric grinder if special care is used. Round (rat tail) file for gullet (radius).


- 1. File each tooth at a 30 degree angle a specific number of times, eg. 4 strokes per tooth. Work your way around the blade until all teeth are sharp.
- 2. DO NOT file the 'gullet' (radius) of the tooth with the flat file. The radius must remain. A sharp corner will lead to a crack and blade failure.

#### IMPORTANT

If an electric grinder is used, use care not to overheat teeth, do not allow tips/tooth to glow red or turn blue. DO NOT place blade in cooling water. This will change the temper of the blade and could result in blade failure.

3. After sharpening teeth, check each tooth radius for evidence of a square (sharp) corner. Use the round (rat tail) file to renew the radius.





## TROUBLESHOOTING

Problem	Check	Status	Cause	Remedy	
	Fuel at carburetor	No fuel at carburetor	Fuel strainer clogged Fuel line clogged Carburetor	Clean or replace Clean or replace See your Echo dealer	
	Fuel at cylinder	No fuel at cylinder	Carburetor	See your Echo dealer	
		Muffler wet with fuel	Fuel Mixture too rich	Open choke Clean/replace air filter Adjust carburetor See your Echo dealer	
		No spark Stop switch off Electrical problem Interlock switch		Turn switch to ON See your Echo dealer See your Echo dealer	
	No spark	Spark gap incorrect Covered with carbon Fouled with fuel Plug defective	Adjust to 0.70mm (0.026 in.) Clean or replace Clean or replace Replace plug		
Air filterEngine runs, but dies or does not accelerate properlyFuel ventSpark PlugCarburetorCooling SystemSpark Arrestor Screen	Air filter	Air filter dirty	Normal wear	Clean or replace	
	Fuel filter	Fuel filter dirty	Contaminants/residues in fuel	Replace	
	Fuel vent	Fuel vent plugged	Contaminants/residues in fuel	Clean or replace	
	Spark Plug	Plug dirty/worn	Normal wear	Clean and adjust or replace	
	Carburetor	Improper adjustment	Vibration	Adjust	
	Cooling System	Cooling system dirty/plugged	Extended operation in dirty/dusty locations	Clean	
		Spark arrestor screen plugged	Normal wear	Replace	
Engine does not crank	N/A	N/A	Internal engine problem	See your Echo dealer	



Fuel vapors are **extremely** flammable and may cause fire and/or explosion. **Never** test for ignition spark near an open spark plug opening, otherwise serious personal injury may result.



## STORAGE



During operation the muffler or catalytic muffler and surrounding cover become hot. Always keep exhaust area clear of flammable debris during transportation or when storing, otherwise serious property damage or personal injury may result.

#### Long Term Storage (over 30 days)

Do not store your unit for a prolonged period of time (30 days or longer) without performing protective storage maintenance which includes the following:

1. Store unit in a dry, dust free place, out of the reach of children.




Do not store in enclosure where fuel fumes may accumulate or reach an open flame or spark.

- 2. Place the stop switch in the "STOP" position.
- 3. Remove accumulation of grease, oil, dirt and debris from exterior of unit.
- 4. Perform all periodic lubrication and services that are required.
- 5. Tighten all the screws and nuts.
- 6. **Drain** the fuel tank **completely** and pull the recoil starter handle several times to remove fuel from the carburetor.

- 7. Remove the spark plug and pour 7 cc (1/4 oz.) of fresh, clean, two-stroke engine oil into the cylinder through the spark plug hole.
  - A. Place a clean cloth over the spark plug hole.
  - B. Pull the recoil starter handle 2-3 times to distribute the oil inside the engine.
  - C. Observe the piston location through the spark plug hole. Pull the recoil handle slowly until the piston reaches the top of its travel and leave it there.
- 8. Install the spark plug (do not connect ignition cable).

#### IMPORTANT

Do not store the unit with tension remaining on the starter spring.



## SERVICING INFORMATION

## PARTS

Genuine ECHO Parts and ECHO REPOWER<sup>TM</sup> Parts and Assemblies for your ECHO products are available only from an Authorized ECHO Dealer. When you do need to buy parts always have the Model Number and Serial Number of the unit with you. You can find these numbers on the engine housing. For future reference, write them in the space provided below.

Model No. \_\_\_\_\_ SN. \_\_\_\_\_

## SERVICE

Service of this product during the warranty period must be performed by an Authorized ECHO Service Dealer. For the name and address of the Authorized ECHO Service Dealer nearest you, ask your retailer or call: 1-800-432-ECHO (3246). Dealer information is also available on our Web Site. When presenting your unit for Warranty service/repairs, proof of purchase is required.

## ECHO CONSUMER PRODUCT SUPPORT

If you require assistance or have questions concerning the application, operation or maintenance of this product you may call the ECHO Consumer Product Support Department at 1-800-673-1558 from 8:30 am to 4:30 pm (Central Standard Time) Monday through Friday. Before calling, please know the model and serial number of your unit to help your Consumer Product Support Representative.

## WARRANTY REGISTRATION

You may register your Echo equipment using the warranty registration card or register on-line at www.echo-usa.com. Registering provides a direct link between you and ECHO if we find it necessary to contact you.

## ADDITIONAL OR REPLACEMENT MANUALS

Safety Manuals in English/Spanish or English/French are available, free of charge, from your ECHO dealer or at www.echo-usa.com.

#### **Operator's and Parts Manuals** are available by:

- Downloading free from www.echo-usa.com
- Purchasing from your Echo Dealer.
- Sending a check or money order for \$2.00 per Parts Catalog or \$1.50 per Operator's Manual made payable to ECHO, INCORPORATED. State on a sheet of paper the model number and serial number of the ECHO unit you have, part number of the manual (if known), your name and address and mail to address below.

Safety Videos are available from your Echo dealer. A \$5.00 shipping charge will be required for each video.


Available Parts Catalog

SRM-211 **№** S/N 06001001 - 06999999

PART NUMBER 99922203252



400 OAKWOOD ROAD LAKE ZURICH, IL 60047 www.echo-usa.com



**DEALER?** Call 1-800-432-ECHO or www.echo-usa.com

CONSUMER PRODUCT SUPPORT 1-800-673-1558 8:30 - 4:30 Mon - Fri C.S.T.

