

POWER PRUNERS®





ECHO Power Pruners provide extra long reach for fast, easy and safe tree pruning while keeping your feet on the ground. Available in either fixed length or telescoping configurations, a Power Pruner can provide a reach of over 12 feet depending on the model (and even longer with optional extensions). The lightweight design and comfortable controls ensure maximum operator comfort. Heavy-duty gearboxes feature dual-sealed bearings and spiral cut steel gears for maximum lubrication, durability and cutting performance. An adjustable oiler delivers the right amount of oil, every time, for exceptional chain lubrication. The chain tensioning system improves cutting performance and extends bar and chain life. ECHO Power Pruners deliver commercial-grade performance and optimum tree care versatility.

POWER PRUNER \over 🕮 🔐





The ergonomic PPF-225 Power Pruner® pole saw features a 94 in. fixed shaft for pruning branches in hard-to-reach places. An i-30™ starter system reduces starting effort by 30%, helping to maximize productivity while minimizing added work. A three-foot shaft extension is also available.

- i-30[™] starter reduces starting effort by 30%
- Front and rear handle rubber grips for operator comfort and reduced vibration
- · Lightweight magnesium gear case with side access chain tensioner
- 3 ft extension also available

| 21.2 | Engine (cc) |
|------------------|-------------------|
| 12.8 | Weight (lbs.) |
| n.) 94 | Overall Length |
| 10 | Bar Length (in.) |
| oz.) 14.2 | Fuel Capacity (|
| oz.) 6.6 | Oil Capacity (fl. |
| | |

MEGHO. **POWER PRUNER® ACCESSORIES**



3 ft. Extension (Fixed only)

Fits all PPF models. Extended reach up to 10 ft. 9 in.

Part#: 99946400011



4 ft. Extension (Telescoping only)

Fits all PPT models. Extended reach up to 16 ft. 2 in.

Part#: 99946400023









The PPF-2620 Power Pruner® pole saw with a 96 in. fixed shaft combines lightweight design, user-friendly ergonomics, and the power you expect from ECHO. Features like two-stage air filtration and a side-access chain tensioner simplify in-field maintenance.

- Front and rear handle rubber grips for operator comfort and vibration reduction
- · Two-stage air filtration system increases cleaning capability and allows for longer maintenance intervals
- Lightweight magnesium gear case with side access chain tensioner
- Automatic, adjustable oiler to match cutting conditions

| Engine (cc) | . 25.4 |
|-------------------------|--------|
| Weight (lbs.) | 13.2 |
| Overall Length (in.) | 96 |
| Bar Length (in.) | 12 |
| Fuel Capacity (fl. oz.) | . 20.6 |
| Oil Capacity (fl. oz.) | 6.6 |







The PPT-2620 Power Pruner* pole saw with loop handle features a telescoping shaft able to reach more than 12 feet. With an ergonomic design, a two-stage air filter and a fuel tank 14% larger than competitors, it's made to handle professional workloads.

- Ergonomic loop handle with rubber grip for comfort and vibration reduction
- Shaft telescopes to over 12 feet in length
- Two-stage air filtration system increases cleaning capability and allows for longer maintenance intervals
- · Automatic, adjustable oiler to match cutting conditions

| Engine (cc) 25.4 | |
|-------------------------------------|--|
| Weight (lbs.) 17.4 | |
| Overall Length (in.) 107-146 | |
| Bar Length (in.) 12 | |
| Fuel Capacity (fl. oz.) 20.6 | |
| Oil Capacity (fl. oz.) | |









The PPT-2620H Power Pruner® pole saw with in-line handle features a telescoping shaft able to reach more than 12 feet. Its ergonomic design, two-stage air filter and larger fuel tank are made to comfortably handle long days and professional workloads.

- In-line handle with rubber grip for comfort and vibration reduction
- Shaft telescopes to over 12 feet in length
- · Two-stage air filtration system increases cleaning capability and allows for longer maintenance intervals
- Automatic, adjustable oiler to match cutting conditions

| Engine (cc) | 4 |
|----------------------------|---|
| Weight (lbs.)1 | 7 |
| Overall Length (in.)107-14 | 6 |
| Bar Length (in.)1 | 2 |
| Fuel Capacity (fl. oz.)20. | 6 |
| Oil Capacity (fl. oz.)6. | 6 |

| | CHAIN | | | | | | | |
|-------------------------|----------------|---------------|-------------|-------------------------|-------------|-------------|--------------|-----------------|
| Power Pruner Models | Length in (cm) | Nose | Bar Part # | Drive Link Count | Gauge (in.) | Pitch (in.) | Chain Part # | File Size (in.) |
| PPF-225, 99944200532 | 10 (25) | Sprocket Nose | 10A0CD3739C | 39 | .050 | 3/8 lp | 91VXL39CQ | 5/32 |
| PPF-2620, PPT-2620/H | 12 (30) | Sprocket Nose | 12A0CD3744C | 44 | .050 | 3/8 lp | 91VXL44CQ | 5/32 |
| PPF-225, 99944200532 | 10 (25) | Sprocket Nose | 10A4CD3739C | 39 | .043 | 3/8 lp | 90PX39CQ | 11/64 |
| PPF-2620, PPT-2620/H | 12 (30) | Sprocket Nose | 12A4CD3744C | 44 | .043 | 3/8 lp | 90PX44CQ | 11/64 |

lp=Low Profile

The part numbers listed above (e.g. 91PXL52CQ) include a two-or three-letter code that references the chain type. See detailed descriptions below.

CHAIN TYPE: LOW-KICKBACK CHAIN

Low-vibration chisel cutters with ramped depth gauges, bumper drive links and standard sequence.

Low-vibration chisel cutters with bumper drive links and standard sequence.

Low-vibration semi-chisel cutter with ramped depth gauges, bumper drive links and longer top plate.

CHAIN TYPE: PROFESSIONAL CHAIN

LPX Round-ground chisel cutters with bumper drive links and standard sequence.

Low-vibration semi-chisel cutter with ramped depth gauges and longer top plate.



| POWER PRUNERS® | PPF-225 | PPF-2620 | PPT-2620 | РРТ-2620Н | |
|--|----------|----------|----------|-----------|--|
| Features and Benefits | <u> </u> | Δ. | Δ. | Δ. | |
| Tool-less air filter cover for easy access | | | | | |
| 2-stage air filter for improved filtration and long engine life | | • | • | • | |
| i-30 [™] starting system for 30% starting effort reduction | | | | | |
| Digital ignition system for easy starting | • | • | • | • | |
| Purge bulb for easy starting | | • | • | • | |
| Galvanized steel tube for rigidity and durability | • | • | | | |
| Aluminum inner drive shaft for torsion strength and lightweight | | | • | • | |
| Ribbed fiberglass outer shaft for rigidity and control | | | • | • | |
| Ergonomic loop handle with rubber grip for comfort and handling | | | • | | |
| In-line handle with rubber grip for comfort | • | • | | • | |
| Shock-absorbing drive shaft prevents damage to shaft | • | • | • | • | |
| Automatic, adjustable oiler to match cutting conditions | • | • | • | • | |
| Side-access chain tensioner for quick chain adjustments | • | • | • | • | |
| Multi-layer flexible cable drive with lifetime warranty for buyer confidence | • | • | • | • | |
| Rubberized front hand grip for comfort and vibration reduction | • | • | | | |
| 1.5:1 gear ratio provides torque needed to cut large branches | • | • | • | • | |
| Telescoping shaft for a variety of cutting heights | | | • | • | |

SPECIFICATIONS

| Model | Engine Disp. (cc) | Starting System | Fuel Cap. (fl. oz.) | Oil Cap. (fl. oz.) | Length Collapsed (in.) | Length Extended (in.) | Optional Extension (ft.) | Bar Length (in.) | Dry Weight* (lbs.) |
|-----------|----------------------|--------------------|------------------------|-----------------------|------------------------------|-----------------------------|--------------------------------|------------------------|--------------------------|
| PPF-225 | 21.2 | i-30 [™] | 14.2 | 6.6 | 94 | - | 3 | 10 | 12.8 |
| PPF-2620 | 25.4 | Standard | 20.6 | 6.6 | 96 | - | 3 | 12 | 13.2 |
| PPT-2620 | 25.4 | Standard | 20.6 | 6.6 | 107 | 146 | 4 | 12 | 17.4 |
| PPT-2620H | 25.4 | Standard | 20.6 | 6.6 | 107 | 146 | 4 | 12 | 17.0 |

*without bar and chain